



**CANTEK**

# JEN60

DRAWER NOTCHER



# JEN60 | DRAWER NOTCHER

## Adding undermount hardware to your cabinet drawers just got easier.

The Cantek JEN60 Drawer Notcher is designed to both notch and drill drawer boxes to install undermount soft-close drawer slides. The operation of the machine is simple with a self-indexing drilling unit that's determined by the position of the drawer for either left or right notching. With a cycle time of approximately 10 seconds per drawer, you can achieve a high throughput and save time for other important tasks.



Drawer sample with left and right drawer notches



2 1/4" wide aluminum body insert knife cutterhead with replaceable carbide insert knives




Insert cutterhead remains below the table under a guard until in operation



Convenient foot pedal operation



Simple drawer location stops and left and right limit switches for drill location



Self-indexing drill unit

## Key Advantages.

- High production capacity of up to 220 drawers machined per hour.
- 57mm (2 1/4") wide cutter head allows you to machine notches for a wide range of undermount drawer slides without needing to change heads or machine the component twice.
- Self-indexing drill unit for left or right drawer notching.
- Convenient foot pedal operation lets operator efficiently load and unload drawers for higher output.
- Pneumatic cutter & drill stroke by foot pedal operation.
- Cutter stroke and drill speed are adjustable for optimum finish results
- Drill will automatically position for both left and right drawer notches by activating a switch in the fence
- Machine will not cycle unless a drawer is up against the switch for safe operation
- Insert knife cutterhead with solid carbide inserts for optimum finish results and long tool life
- 2 1/4" (57mm) wide cutter allows for a wide range of undermount slides
- Comes with insert cutterhead with inserts and 1/4" (6.3mm) solid carbide drill bit.
- Capable of notching up to 220 drawer boxes (both left and right) per hour.

## Specifications.

Main cutter motor	3 HP
Notch dimensions	2 1/4" (57mm) x 0.5" high
Cutter diameter	10"
Drill diameter	1/4"
Table size	49" x 22"
Table height from floor	32"
Dust port	2 x 4" (1,340 CFM requirement)
Compressed air required	90 – 100 PSI
Machine dimensions	48" x 37 3/4" x 39 3/4"
Machine weight	506 lbs.